



HENRIK LINDER FROM DIRTY LOOPS

**WE TAKE THE LOWER NOTES TO A HIGHER LEVEL.**

IF YOU PLAY YOUR BASSGUITAR BY HAND, OF COURSE IT SHOULD BE MADE BY HAND.  
+46(0)76-0258106 INFO@MATTISSONBASS.SE WWW.MATTISSONBASS.SE

## Features

Modular onboard bass preamp with 1-band active filter. Selectable frequency. Very low noise amplifiers with flat response. Low power consumption. Designed to work with either one or two 9V batteries, +6dB headroom in 18-V operation. Potentiometer with center detent.

Boost and cut filter : Middle +/- 15 dB @ 400Hz / 650Hz / 1000Hz

## Specifications

Test conditions:  $V_{cc}=18V$ ,  $T=22^{\circ}C$ ,  $V_{in}=1Vp-p@1kHz$

Operating voltage	6-20 V
Battery life	800 h
Input impedance	620 k $\Omega$
Output impedance	<1 k $\Omega$
Bandwidth -3dB	0,3 Hz - 40 kHz
Noise (20-20k Hz)	< -98 dBu
Distortion (THD)	< 0,003%
Dimensions (l,w,h)	33 x 20 x 25 mm
Wire length	10 cm
Pot (length, diameter)	Bushing 10 x 7 mm, Shaft 10 x 6 mm

## Frequency selection

 400 Hz

 650 Hz

 1000 Hz